



9460

All new and more powerful 9460 Remote Area Lighting System (RALS) provides convenient and ecologically responsible alternatives to wasteful generator powered lights. Engineered with the Intelligent Control System which calculates and displays current battery life. Additionally, it allows the user to regulate the intensity of the light, choose the desired run time or select from three pre-set power levels. Built with versatility in mind, the 9460 RALS features two telescopic masts (each extends to nearly 6 feet) and two 360° articulating light heads. The system's next-generation LEDs combine to radiate up to 12,000 lumens (6,000 per light head). For extended applications, the 9460 can run continuously on wall power. The ability to leave on charge allows you to always be prepared. A 12volt power port including a dual USB adapter provides power for multiple peripheral devices. Built self-contained in a tough-as-nails Peli case, the 9460 is compact and provides easy ground transport with a retractable pull handle and stainless steel ball-bearing polyurethane wheels.

CAUTION: The Peli Products RALS models 9460 and 9470 contain sealed lead acid batteries that can generate hydrogen gas when charging. It is imperative that these products are charged, as instructed, with the case lid open to allow any gases to escape as charging with the lid closed poses a significant hazard. Failure to abide by this instruction could result in injury and/or damage to property. Please refer to the warnings provided in the instructions for the unit and on a decal affixed to the inside of the case adjacent to the cavity where the charger unit is packed.

NEW UPGRADED SPECS

- Телескопические сдвоенные осветительные светодиодные головки
- Размещается в защитном корпусе Peli
- Бесшумная работа
- Низкая рабочая температура
- Никаких выхлопов
- Полная индикация уровня заряда батареи с мигающим индикатором низкого уровня
- Upright and lie flat pole brackets
- Dual USB power adapter
- RoHS and CE Compliant



РАЗМЕРЫ

Head (LxWxD)	8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm)
Closed (LxWxD)	23.25 x 14.00" x 9.25 (59.1 x 35.6 x 23.5 cm)
длина мачты	79.50" (201.9 cm)
Длина шнура	13.78" (35 cm)

МАТЕРИАЛЫ

корпус	Polypropylene
Головка	Aluminum
Стойка	Aluminum
линза	Polycarbonate (PC)

ЦВЕТА

 Black	 Yellow
---	--

LIGHT SPECS

лм высокий	12000
-------------------	-------

головки ламп	2
тип лампы	LED
количество светодиодов	20
диапазон луча	120°
Класс защиты IP	54

POWER

время работы высокий	3.00 hrs
время работы низкий	24.00 hrs
тип батареи	Sealed Lead Acid (SLA)
Rechargeable	да
ресурс аккумуляторных батарей	500 cycles
время зарядки	8 hrs
Индикатор заряда батареи	iControl
гнезда основные	2
вольт	12.0v

ВЕС

масса	61.00 lbs (27.7 kg)
--------------	---------------------

SWITCH

тип выключателя	iControl Keypad
------------------------	-----------------

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-20-24