



1510SC

Protector

Studio Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **2 in 1 protection: detachable computer sleeve and accessories pouch**

- Maximum airline carry on size*

- **Strong polyurethane wheels with stainless steel bearings**

- **Watertight, crushproof, and dustproof**

- Automatic pressure equalization valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded top and side handles

- Easy open double-throw latches

- O-ring seal

- Open cell core with solid wall design - strong, light weight

- Retractable extension trolley handle

- Fits notebook computers up to 14.4" x 11.1" x 1.7" (36.58 x 28.19 x 4.32 cm)

- Peli's legendary lifetime guarantee**

- * Check with your airline for exact measurement requirements.

- * Where applicable by law



DIMENSIONS

Interior (LxWxD)	19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm)
Exterior (LxWxD)	22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm)
Lid Depth	1.79" (4.5 cm)
Bottom Depth	5.79" (14.7 cm)
Total Depth	7.58" (19.3 cm)
Int Volume	0.96 ft³ (0.027 m³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	13.60 lbs (6.2 kg)
Weight Empty	11.99 lbs (5.4 kg)
Buoyancy	64.15 lbs (29.1 kg)
Master Pack Weight	32.43 lbs (14.7 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

Wheels	2
Extendable Handle	yes
Master Pack	2
Nameplate	yes
Reduced Area	yes
Military	yes

ACCESSORIES



1513
Replacement O-ring



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 06-01-24