

2410Z0 StealthLite™

Same features as the StealthLiteTM 2400 but with the LED module that produces a true, bright collimated LED beam. The StealthLiteTM 2410Z0 LED Zone 0 is corrosion proof, resistant to extreme temperatures, and submersible. It is powered by 4 AA alkaline cells and certified to ATEX Zone 0 (Category 1).



DIMENSIONS

| Length | 7.00" (17.8 cm) |
|--------------------------------|------------------------------------|
| MATERIALS | |
| Body | Anti-static Impact Modified PC/PBT |
| O-Ring | Ethylene Propylene |
| Lens | Anti-static PMMA |
| Shroud | Anti-static Impact Modified PC/PBT |
| Contact Spring Retainer | Stainless Steel / Phosphore Bronze |
| | |
| COLOURS | |

High Visibility Yellow

LIGHT SPECS

Lamp Type

LED

POWER

| Battery Size | AA |
|-------------------------|----------|
| Battery Type | Alkaline |
| Battery Quantity | 4 |
| Volts | 6.0v |
| | |

WEIGHT

| Weight With Batteries | 7.3 oz (207 gr) |
|-----------------------------|-----------------|
| Weight Without Batteries | 3.7 oz (105 gr) |
| Packaged Weight | 8.4 oz (238 gr) |

SWITCH

| Switch Type | One-handed Safety Switch |
|-------------|--------------------------|
| Light Modes | On / Off |

CERTIFICATIONS

ATEX Zone 0

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 06-02-24

OTHER

Minimum Pack6Package CodeB

| FL1 STANDARD | HIGH |
|--------------|---------------|
| 3MZ | 153 LUMENS |
| | 5h 45mins |
| | 165m |
| | 6837cd |
| | IPX7 |

ACCESSORIES