



## 3410M

### Right Angle Light

**The most versatile pro-grade flashlight in the world, with magnet clip.**

The 3410M (magnet version) is the ultimate compact work light. Molded from "glow in the dark" photoluminescent material, this light is easy to find even when it's off. The 3410M is equipped with both a spot and flood LED for close-up as well as distance, so you can have wide area light in the immediate work area and still penetrate darkness hundreds of yards away. It can be activated to run one or both LEDs with 3 levels of brightness. The articulating head and built-in clip allows the light to be directed wherever it is needed, while a heavy duty magnet allows the light to be snapped to steel surfaces.

The Peli 3410M- a professional grade multi-task lighting tool that will help you get the job done- under any circumstances.

- "Glow in the Dark" Body
- 3 modes: Spot, Flood or Both
- Articulating Light Head
- Attached clip with integrated magnet
- 3 Light Levels (High, Medium, Low)
- Security Lanyard

#### DIMENSIONS

**Length:** 7.44" (18.9 cm)

#### MATERIALS

**Body:** Photo luminescent Polycarbonate (PC)

**O-Ring:** NBR

**Lens:** Clear Polycarbonate (PC)

**Shroud:** Photo luminescent Polycarbonate (PC)

**Clip:** Photo luminescent Polycarbonate (PC)

**Contact Spring Retainer:** Stainless Steel / Phosphore Bronze / Brass Nickel Plate






#### COLOURS

 Photoluminescent

## LIGHT SPECS

Lamp Type: LED

Lamp Secondary Type: LED

FL1 STANDARD	MAIN HIGH	MAIN MED	MAIN LOW
	653 LUMENS	97 LUMENS	25 LUMENS
	5h 0mins	19h 0mins	61h 0mins
	184m	67m	34m
	8504cd	1129cd	292cd
	IPX8 (1m)		

## POWER

Battery Size: AA

Battery Type: Alkaline

Battery Quantity: 3

Volts: 4.5v

## WEIGHT

Weight With Batteries: 9.9 oz (281 gr)

Weight Without Batteries: 7.4 oz (210 gr)

## SWITCH

Switch Type: Push Button

Light Modes: High / Medium / Low

Peli Products, S.L.U.

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)