CLASSIC-V-SERIES-5U

Classic V

5U

• Engineered to provide secure transport for rack mountable electronics
• Available in 3U, 4U, 5U, 7U, and 9U
• Equipment payload weight ranges for 3U – 5U = 80-100 lbs. (36-45 kg) per case
• Equipment payload weight ranges for 7U – 9U = 100-170 lbs. (45-77 kg) per case
• Black case with Anti-Reflective zinc cobalt black (HCB) catch-and-strike hardware
• 2 Lockable Cable Catches per lid to provide security for your equipment
• Black stainless steel handles
• Molded stacking ribs and coupling catches to secure cases when stacked
• Lid hangers for lid storage while in use
• 19" (48 cm) wide, 33" (83 cm) deep fixed square hole frame for universal equipment fit
• Choice of SAE 10-32 or Metric M6 clip nuts
• Sealed gasket and PRV keeps container watertight and eliminates over pressurization
• 4 removable 3.5" (8.9 cm) heavy duty bottom casters
• REACH and RoHs compliant



DIMENSIONS

Exterior (L×W×D)	45.80 x 27.00" x 16.60 (116.3 x 68.6 x 42.2 cm)
Rack Height	8.75" (22.2 cm)
Rack Depth	33.00" (83.8 cm)
Interior Lid Depth	2.50" (6.4 cm)
Interior Back Lid Depth	5.25" (13.3 cm)

MATERIALS

Body	RotoMolded Polyethylene
O-Ring	Silicone Sponge
Purge Body	Aluminum
Hardware	Stainless Steel (Black Oxide) / RoHs Nickel Black
Frame	Steel (Clear Coated)

COLOURS

■ Black

WEIGHT

Weight	56.00 lbs (25.4 kg)

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com