



## TL3619

Trunk Locker

- Molded-in rib design provides secure stacking and interlock
- Two organization trays
- Two press & pull latches
- Water resistant
- Good for General storage, Tool storage, or Emergency preparedness supplies



### DIMENSIONS

|                         |                                                |
|-------------------------|------------------------------------------------|
| <b>Interior (L×W×D)</b> | 32.88 x 15.00" x 17.75 (83.5 x 38.1 x 45.1 cm) |
| <b>Exterior (L×W×D)</b> | 36.27 x 18.50" x 19.56 (92.1 x 47 x 49.7 cm)   |
| <b>Int Volume</b>       | 5.07 ft <sup>3</sup> (0.144 m <sup>3</sup> )   |

### MATERIALS

|                   |                                              |
|-------------------|----------------------------------------------|
| <b>Body</b>       | Injection Molded HPX™ high performance resin |
| <b>Latch</b>      | Valox - Polybutylene Terephthalate (PBT)     |
| <b>O-Ring</b>     | Silicone Sponge                              |
| <b>Pins</b>       | Stainless Steel                              |
| <b>Pins (Alt)</b> | Aluminum with Type II Anodized               |
| <b>Foam</b>       | 2.0PCF polyethylene                          |
| <b>Purge Body</b> | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Vent</b> | Gortex membrane                              |

### COLOURS

 OD Green

### WEIGHT

|                     |                       |
|---------------------|-----------------------|
| <b>Weight Empty</b> | 26.00 lbs (11.8 kg)   |
| <b>Buoyancy</b>     | 448.19 lbs (203.3 kg) |

### TEMPERATURE

|                            |                |
|----------------------------|----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)  |

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 04-20-24*