



## iM2450 Storm

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



### CONFIGURATIONS



**iM2450**  
Standard



**iM2450-X0000**  
No Foam



**iM2450-X0002**  
With Padded Dividers



**iM2450-X0001**  
With Foam

### DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (L×W×D)</b>      | 18.00 x 13.00" x 8.40 (45.7 x 33 x 21.3 cm)   |
| <b>Exterior (L×W×D)</b>      | 19.20 x 15.20" x 9.00 (48.8 x 38.6 x 22.9 cm) |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                |
| <b>Bottom Depth</b>          | 6.40" (16.3 cm)                               |
| <b>Total Depth</b>           | 8.4" (21.3 cm)                                |
| <b>Int Volume</b>            | 1.14 ft <sup>3</sup> (0.032 m <sup>3</sup> )  |
| <b>Padlock Hole Diameter</b> | 0.38" (1 cm)                                  |

### MATERIALS

|                         |  |
|-------------------------|--|
| <b>Body</b>             | Injection Molded HPX™ high performance resin |
| <b>Latch</b>            | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Latch (Alt)</b>      | Xenoy - Polyester/Polycarbonate blend        |
| <b>O-Ring</b>           | EPDM   |
| <b>Pins</b>             | Stainless Steel                              |
| <b>Pins (Alt)</b>       | Aluminum                                     |
| <b>Foam</b>             | 1.3/1.35 polyester                           |
| <b>Purge Body</b>       | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Body (Alt)</b> | Xenoy - Polyester/Polycarbonate blend        |
| <b>Purge Vent</b>       | Gortex membrane                              |

## COLOURS

■ Black

■ OD Green

## WEIGHT

|                           |                      |
|---------------------------|----------------------|
| <b>Weight With Foam</b>   | 8.90 lbs (4.04 kg)   |
| <b>Weight Empty</b>       | 7.40 lbs (3.36 kg)   |
| <b>Buoyancy</b>           | 70.86 lbs (32.14 kg) |
| <b>Master Pack Weight</b> | 31.00 lbs (14.06 kg) |

## TEMPERATURE

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -20°F (-28.9 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)    |

## CERTIFICATIONS

**IP67**

## OTHER

|                    |     |
|--------------------|-----|
| <b>Master Pack</b> | 3   |
| <b>Military</b>    | yes |

## ACCESSORIES



**iM24XX-PHOTAPALLET**  
Photography Pallet



**iM2450-FOAM**  
5 pc. Replacement Foam Set




**iM-STRAP-S-VER2**  
Padded Shoulder Strap



**iM-LIDSTAY**  
Lid Stay



**iM24XX-LIDORG**  
Lid Organizer




**iM2450-TREK**  
TrekPak Case Divider Kit




**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**iM2450-M4-BEZEL-L**  
Lid Bezel Kit (Metric)



**iM2450-MBEZ-B**  
Base Bezel Kit (Metric)



**IM2500TPDIV**  
Extra TrekPak Dividers

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 05-08-26*