

9440

NOW TWICE AS BRIGHT

The 9440 now offers three pre-set power levels, battery level indication and comes equipped with a lithium ion rechargeable battery. The 9440 moves fast to light up ravines, confined spaces, riverbanks, anyplace generator lights can't go. Deployed, the mast extends 7 feet (2.1 meters) high, shining light over low obstructions encountered by traditional lantern style lights. With a 125 degree beam spread and up to 5300 lumens, your entire work area will have the light you need for a safe and efficient operation. The 9440 is able to run directly from wall power if needed and can be left on charge indefinitely which makes for an invaluable emergency preparedness tool.

The 9440 is maintenance free, using super tough LED lamp modules and a lithium ion battery for up to 8 hours of continuous light.

Adjustable carrying strap included.

- · Built Peli tough
- Convenient shoulder strap
- RoHS and CE Compliant
- Equipped with a lithium ion rechargeable battery
- Mast extends 7 feet (2.1 meters) high when deployed
- Up to 5300 lumens
- Up to 8 hours run time



DIMENSIONS

Head (L×W×D)	7.87 x 7.87" x 3.50 (20 x 20 x 8.9 cm)
Closed (L×W×D)	37.40 x 7.87" x 7.87 (95 x 20 x 20 cm)
Full (L×W×D)	85.00 x 35.83" x 35.83 (215.9 x 91 x 91 cm)

Light Head Height

(max)

85.00" (215.9 cm)

MATERIALS

Body	Polypropylene
Head	Polycarbonate (PC) / ABS

Mast Aluminum

Lens Polycarbonate (PC)

COLOURS

Black Yellow

LIGHT SPECS

Lumens (High)	5300
Lumens (Med)	2800
Lumens (Low)	1400
Lamp Heads	1
Lamp Type	LED
Number of LEDs	12
Beam Spread	125°
IP Rating	65

POWER

Run Time (High)1.50 hrsRun Time (Med)4.00 hrsRun Time (Low)8.00 hrsBattery TypeLithium-lonRechargeableyes

Battery Lifespan 500 cycles
Charge Time 3 hrs 45 mins
Battery Level Indicator Level indicator

WEIGHT

Weight 16.09 lbs (7.3 kg)

SWITCH

Switch Type Silicone Rubber Keypad

ACCESSORIES





9447 DC Vehicle Charger Cord

9483 Power Supply

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 05-03-24