# 0340

## Protector

Cube Case



Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.
Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Built-in, spring loaded pull handle**
- **Large 2-person fold down handles**
- **Stainless steel caster wheels included**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Ultra-tough HPX$^{P}$ Polymer Construction

## CONFIGURATIONS



**0340**
Standard



**0344**
With Padded Dividers



**0340NF**
No Foam



**0340WF**
With Foam

## DIMENSIONS

| | |
|---|---|
| **Interior (L×W×D)** | 18.00 x 18.00" x 18.00 (45.7 x 45.7 x 45.7 cm) |
| **Exterior (L×W×D)** | 20.50 x 20.50" x 19.25 (52.1 x 52.1 x 48.9 cm) |
| **Lid Depth** | 4.50" (11.4 cm) |
| **Bottom Depth** | 13.50" (34.3 cm) |
| **Total Depth** | 18" (45.7 cm) |
| **Int Volume** | 3.38 ft³ (0.096 m³) |
| **Padlock Hole Diameter** | 0.31" (0.8 cm) |

## MATERIALS

| | |
|---|---|
| **Body** | Polypropylene |
| **Latch** | ABS |
| **O-Ring** | Polymer |
| **Pins** | Stainless Steel |

| | |
|---|---|
| **Foam** | 1.3 lb Polyurethane |
| **Purge Body** | ABS |
| **Purge Vent** | 3 Micron Hydrophobic Non-Woven |

## COLOURS

Black

## WEIGHT

| | |
|---|---|
| **Weight With Foam** | 29.76 lbs (13.5 kg) |
| **Weight Empty** | 24.00 lbs (10.89 kg) |
| **Buoyancy** | 220.46 lbs (100 kg) |
| **Master Pack Weight** | 32.24 lbs (14.62 kg) |

## TEMPERATURE

| | |
|---|---|
| **Minimum Temperature** | -40°F (-40 °C) |
| **Maximum Temperature** | 190°F (87.8 °C) |

## CERTIFICATIONS

**IP67**
**Def Stan 81-41**

## OTHER

| | |
|---|---|
| **Wheels** | 4 |
| **Master Pack** | 1 |
| **Nameplate** | yes |
| **Reduced Area** | yes |
| **Military** | yes |

## ACCESSORIES



**0341**
7 pc. Replacement Foam Set



**0343**
Replacement O-ring



**0345**
Padded Divider Set



**0357**
Cube Case Mobility Package



**1507QM**
Quick Mounts - set of 4

**Pelican**
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

*Document created on 10-31-26*