# 3325

**Compact / Safety Certified / Tail Switch Design** - All three are combined in the 3325 LED flashlight
The compact and lightweight design begins with the use of only 3 AA alkaline batteries and yet produces over 162 lumens of brilliant light. Safety certified for use in most volatile work environments. The rear mounted switch make the 3325 a perfect match for any helmet mounted applications. The photoluminescent (“glow in the dark”) shroud ensures you’ll be able to locate your light even in the darkest of conditions. For added reliability, an IPX7 ingress protection level will protect the 3325 in the most severe weather conditions. Backed by Pelican’s Lifetime Guarantee makes the 3325 a true value!




- 3 AA Batteries (Included)
- Glow-in-the-dark shroud
- Tail switch for easy one-handed operation
- Pelican Products, Inc.'s Lifetime Guarantee
- Ingress Protected IPX7
- Class I, Class II, Class III – Division 1 Safety Certified

## DIMENSIONS

| | |
|---|---|
| **Length** | 6.06" (15.4 cm) |

## MATERIALS

| | |
|---|---|
| **Body** | EXL |
| **O-Ring** | EPDM |
| **Lens** | Polycarbonate (PC) |
| **Shroud** | Photo luminescent Polycarbonate (PC) |

## COLOURS

High Visibility Yellow

## LIGHT SPECS

| | |
|---|---|
| **Lamp Type** | LED |

## POWER

| | |
|---|---|
| **Battery Size** | AA |
| **Battery Type** | Alkaline |
| **Battery Quantity** | 3 |
| **Batteries Included** | yes |
| **Volts** | 4.5v |

## WEIGHT

| | |
|---|---|
| **Weight With Batteries** | 6.1 oz (173 gr) |
| **Weight Without Batteries** | 3.6 oz (102 gr) |

## SWITCH

| | |
|---|---|
| **Switch Type** | Push Button |
| **Light Modes** | On / Off |

**Pelican**
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com


*Document created on 10-31-26*

## CERTIFICATIONS

**Class I, Division 1**
**IECEx ia**
**Class II, Division 1**
**Class III, Division 1**

## OTHER

| | |
|---|---|
| **Minimum Pack** | 1 |
| **Package Code** | C |

| FL1 STANDARD | HIGH |
|---|---|
|  | 171 LUMENS |
|  | 16h 0mins |
|  | 136m |
|  | 4558cd |
|  | IPX7 |

## ACCESSORIES