



## 2745

### Headlamp

Pelican™ safety approved headlamps are designed for use in hazardous environments. It is not only Class I Div 1 approved but also is ultra compact and lightweight. Equipped with three LEDs, it produces up to 33 lumens and provides up to 40 hours of run time and offers multiple modes (high, low, flashing). The Pelican 2745 is available in two colors (yellow or black). Count on Pelican to bring you the best in lighting design and technology.

The new Pelican™ 2745 headlamp: Guiding you safely through the danger zone.

- Built Pelican tough
- Hands-free design
- Comfortable Cloth Strap
- Safety Certified - Class I, Division I



### DIMENSIONS

<b>Length</b>	2.25" (5.7 cm)
---------------	----------------

### MATERIALS

<b>Body</b>	Polycarbonate (PC)
<b>O-Ring</b>	Over-molded TPR
<b>Lens</b>	Polycarbonate (PC)
<b>Shroud</b>	Polycarbonate (PC)

### COLOURS

<span style="background-color: black; width: 10px; height: 10px; display: inline-block;"></span> Black	<span style="background-color: yellow; width: 10px; height: 10px; display: inline-block;"></span> High Visibility Yellow
--	--

### LIGHT SPECS

<b>Lamp Type</b>	LED
------------------	-----

### POWER

<b>Battery Size</b>	AAA
<b>Battery Type</b>	Alkaline
<b>Battery Quantity</b>	3
<b>Batteries Included</b>	yes
<b>Volts</b>	4.5v

### WEIGHT

<b>Weight With Batteries</b>	3.3 oz (94 gr)
<b>Weight Without Batteries</b>	2.0 oz (57 gr)

### SWITCH


<b>Switch Type</b>	Push Button
--------------------	-------------

**Light Modes**

High / Low / Flashing

**CERTIFICATIONS****Class I, Division 1****IECEx ia****InMetro****OTHER****Minimum Pack**

1

FL1 STANDARD	HIGH	LOW
	33 LUMENS	17 LUMENS
	20h 0mins	40h 0mins
	35m	25m
	309cd	155cd
	IP54	

**ACCESSORIES**

**2748**  
Strapless Headlamp Adapter

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 02-16-26*