1660
Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.
Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.



- Personalized nameplate service available
- **4 strong polyurethane wheels with stainless steel bearings**
- **Large 2-person fold down handles**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Ultra-tough HPX^{P} Polymer Construction

CONFIGURATIONS



1660
Standard



1664
With Padded Dividers



1660NF
No Foam



1660WF
With Foam

DIMENSIONS

Interior (L×W×D)	28.20 x 19.66" x 17.63 (71.6 x 49.9 x 44.8 cm)
Exterior (L×W×D)	31.59 x 22.99" x 19.48 (80.2 x 58.4 x 49.5 cm)
Lid Depth	3.50" (8.9 cm)
Bottom Depth	14.14" (35.9 cm)
Total Depth	17.64" (44.8 cm)
Int Volume	5.66 ft³ (0.16 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

Black | Desert Tan | OD Green

WEIGHT

Weight With Foam	42.16 lbs (19.12 kg)
Weight Empty	34.16 lbs (15.49 kg)
Buoyancy	365.00 lbs (165.56 kg)
Master Pack Weight	49.00 lbs (22.23 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

Wheels	4
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Reduced Area	yes
Military	yes

ACCESSORIES



1661
5 pc. Replacement Foam Set



1662
Pick N Pluck™ Sections Only (set of 3)



1663
Replacement O-ring



1665
Padded Divider Set



1669
Photo/Lid Organizer



1507QM
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 10-31-26