



2010Z0 SabreLite™

The SabreLite™ 2010Z0 LED is Peli's flagship LED torch. The rugged, light weight anti-static PC/PBT resin body is submersible to 1 meter for 30 mins (IPX7) and a twist on/off lens shroud eliminates accidental discharge. It is powered by 3 C alkaline cells. The SabreLite™ 2010Z0 is the future of LEDs. Certified to ATEX Zone 20.




DIMENSIONS

| | |
|---------------|-----------------|
| Length | 8.11" (20.6 cm) |
|---------------|-----------------|

MATERIALS

| | |
|--------------------------------|------------------------------------|
| Body | Anti-static PC/PBT |
| O-Ring | Ethylene Propylene |
| Lens | Anti-static PMMA |
| Shroud | Anti-static Impact Modified PC/PBT |
| Clip | Anti-static Impact Modified PC/PBT |
| Contact Spring Retainer | Stainless Steel / Brass Nickel |

COLOURS

| |
|--|
|  High Visibility Yellow |
|--|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|-------------------------|----------|
| Battery Size | C |
| Battery Type | Alkaline |
| Battery Quantity | 3 |
| Volts | 4.5v |

WEIGHT

| | |
|---------------------------------|------------------|
| Weight With Batteries | 13.4 oz (380 gr) |
| Weight Without Batteries | 5.4 oz (153 gr) |

SWITCH






| | |
|--------------------|----------------------|
| Switch Type | Twisting Lens Shroud |
| Light Modes | On / Off |

CERTIFICATIONS

ATEX Zone 0

OTHER

| | |
|--------------|-----|
| Submersible | yes |
| Minimum Pack | 1 |
| Package Code | C |

| FL1 STANDARD | HIGH |
|---|---------------|
|  | 129 LUMENS |
|  | 22h 0mins |
|  | 135m |
|  | 4582cd |
|  | IPX7 |