



# 1460TOOL

## Protector

Mobile Tool Chest

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Also available without tray dividers
- **Adjustable and removable tray dividers for easy customization**
- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Easy open double-throw latches
- O-ring seal for dust and water resistant seal (IP66)
- Open cell core with solid wall design - strong, light weight
- Tray sizes: Top tray 17.65" x 8.2" x 2.4" (44.83 x 20.83 x 6.10 cm) and bottom tray 17.3" x 8.0" x 2.3" (43.94 x 20.32 x 5.84 cm)
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



## DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (LxWxD)</b>      | 18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm) |
| <b>Exterior (LxWxD)</b>      | 20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)  |
| <b>Lid Depth</b>             | 4.91" (12.5 cm)                               |
| <b>Bottom Depth</b>          | 6.01" (15.3 cm)                               |
| <b>Total Depth</b>           | 10.92" (27.7 cm)                              |
| <b>Int Volume</b>            | 1.16 ft³ (0.033 m³)                           |
| <b>Padlock Hole Diameter</b> | 5/16" (12.7 cm)                               |

## MATERIALS

|                   |                                |
|-------------------|--------------------------------|
| <b>Body</b>       | Polypropylene                  |
| <b>Latch</b>      | EXL                            |
| <b>O-Ring</b>     | Polymer                        |
| <b>Pins</b>       | Stainless Steel                |
| <b>Foam</b>       | Polyurethane                   |
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

## COLOURS

■ Black

## WEIGHT

|                         |                     |
|-------------------------|---------------------|
| <b>Weight With Foam</b> | 13.00 lbs (5.9 kg)  |
| <b>Buoyancy</b>         | 82.00 lbs (37.2 kg) |

TEMPERATURE

---

**Minimum Temperature**    -40°F (-40 °C)  
**Maximum Temperature**    190°F (87.8 °C)

CERTIFICATIONS

---

**IP66**

OTHER

---

**Nameplate**                    yes  
**Military**                      yes

ACCESSORIES

---



**1463**  
Replacement O-ring



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

---

**Peli**  
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 09-07-25*