

1506

Air

Peli understands that finding the right protection, with the perfect fit for your gear, is a priority. Peli™ Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Peli's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Peli's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Peli has you covered.

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- \bullet Super-light proprietary HPX Polymer makes this case up to 40% lighter than the competition
- Limited Lifetime Warranty
- Super-light proprietary HPX^{2™} Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck[™] foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



CONFIGURATIONS



1506 Standard



1506WF With Foam



1506NF No Foam



1506TPWith TrekPak Divider System

DIMENSIONS

Interior (L×W×D) 18.70 x 9.40" x 7.80 (47.5 x 23.9 x 19.8 cm) Exterior (L×W×D) 20.12 x 12.02" x 8.56 (51.1 x 30.5 x 21.7 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 5.80" (14.7 cm)

 Total Depth
 7.8" (19.8 cm)

 Int Volume
 0.79 ft³ (0.022 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Proprietary Polypropylene Blend

Latch ABS
O-Ring EPDM
Purge Body ABS

Purge Vent Hi-Flow

Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

 Weight With Foam
 6.30 lbs (2.9 kg)

 Weight Empty
 5.35 lbs (2.4 kg)

 Buoyancy
 51.69 lbs (23.4 kg)

TEMPERATURE

 $\begin{array}{ll} \mbox{Minimum Temperature} & -60\,^{\circ}\mbox{F} \; (-51.1\,^{\circ}\mbox{C}) \\ \mbox{Maximum Temperature} & 160\,^{\circ}\mbox{F} \; (71.1\,^{\circ}\mbox{C}) \\ \end{array}$

ACCESSORIES



1506AirFS 4 pc. Replacement Foam Set

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 05-11-24