


# 5050R

Get local to long distance in a slide. The new Peli<sup>™</sup> 5050R flashlight features flood to spot technology: Flood position projects a wide beam to illuminate your work area and spot beam for a long distance focused beam. Get power for the work day and your smartphone. Recharge the 5050R by connecting directly to its Micro USB port. Or connect to a USB port to power your smartphone or any other USB powered device. The 5050R: it's our reachargeable option that can add some jolt to your text conversations.



- 4 modes: Boost / High / Low / Flashing
- Up to 201m Beam Distance
- Up to 883 Lumens

#### DIMENSIONS

#### Length

6.16" (15.6 cm)

## MATERIALS

Body	Aluminum with Type II Anodized
O-Ring	NBR
Lens	AR Coated Glass
Shroud	Aluminum with Type II Anodized

### COLOURS

Black

## LIGHT SPECS

Lamp Type LED

## POWER

Battery Size	18650
Battery Type	Lithium
Battery Quantity	1
Batteries Included	yes
Rechargeable	yes
Charge Time	6 hrs
Battery Level Indicator	Full-time battery indicator
Volts	3.7v

# WEIGHT

Weight With Batteries	5.8 oz (164 gr)
Weight Without Batteries	4.1 oz (116 gr)



SWITCH	S	W	I-	T(	Cŀ	Η
--------	---	---	----	----	----	---

Switch Type Light Modes Push Button Boost / High / Low / Flashing

FL1 STANDARD	HIGH	LOW	BOOST
J'AZ	393 LUMENS	21 LUMENS	883 LUMENS
	2h 30mins	40h 0mins	0h 0mins
	134m	30m	201m
	4488cd	224cd	10093cd
- Charles	IPX8 (1m)		

ACCESSORIES



2389 Replacement Battery

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 05-09-24