AL4824-1604

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.



• Lignes de partage résistantes aux éclaboussures avec joints à rainure et languette moulés étroitement serrés en permanence, même
• Angles et bords renforcés pour protection additionnelle contre les impacts
• Épaulements et cannelures moulées pour empilement sûr et sans glissement, plus de force colonnaire et protection renforcée
• Matériel encastré pour une protection renforcée
• Verrous anti-tiraillement positif prévenant la séparation du couvercle après impact et réduisant les contraintes sur le matériel
• Inserts métalliques surmoulés brevetés aux points d'attache pour fermeture et charnière pour une meilleure résistance
• Construction monobloc, moulée à partir de polyéthylène léger résistant aux chocs

CONFIGURATIONS



AL4824-1604
Standard

AL4824-1604-RP
Empty

AL4824-1604RPC
No Foam, With Casters

AL4824-1604RPFC
With Foam, With Casters

DIMENSIONS

INTÉRIEUR	48.60 x 24.60" x 20.20 (123.4 x 62.5 x 51.3 cm)
EXTÉRIEUR	51.70 x 27.80" x 23.70 (131.3 x 70.6 x 60.2 cm)
profondeur couvercle	4.10" (10.4 cm)
profondeur fond	16.10" (40.9 cm)
profondeur totale	20.2" (51.3 cm)
Volume intérieur	13.98 ft³ (0.396 m³)

MATÉRIAUX

Corps	RotoMolded Polyethylene
loquet	Steel (Nickel-black Plated)
joint torique	Silicone Sponge
mousse	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined
corps de purge	Aluminum
poignée	Heavy Duty Injection Molded Standard
matériel	Yellow Carbon Steel Standard

COULEURS

Gray - 133 Fed Std 26270

POIDS

poids	57.30 lbs (25.99 kg)
flottabilité	1146.02 lbs (519.83 kg)
Master Pack Weight	59.30 lbs (26.9 kg)

TEMPÉRATURE

température minimale	-20°F (-28.9 °C)
température maximale	140°F (60 °C)

AUTRES

Domaine militaire	Oui

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 10-31-26