



iM2600 Storm

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Guaranteed for life
- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM2600
Standard



iM2600-X0000
No Foam



iM2600-X0002
With Padded Dividers



iM2600-X0001
With Foam



WHISKY-MULTIB
Quad Whiskey

DIMENSIONS

Interior (L×W×D)	20.00 x 14.00" x 7.70 (50.8 x 35.6 x 19.6 cm)
Exterior (L×W×D)	21.20 x 16.00" x 8.30 (53.8 x 40.6 x 21.1 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	5.70" (14.5 cm)
Total Depth	7.7" (19.6 cm)
Int Volume	1.25 ft ³ (0.035 m ³)
Padlock Hole Diameter	0.28" (0.7 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

■ Black

■ OD Green

■ Yellow

WEIGHT

Weight With Foam	11.60 lbs (5.26 kg)
Weight Empty	8.50 lbs (3.86 kg)
Buoyancy	79.81 lbs (36.2 kg)
Master Pack Weight	24.20 lbs (10.98 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)


CERTIFICATIONS

IP67


OTHER

Master Pack	2
Military	yes

ACCESSORIES



iM2600-BEZEL-LID
Lid Bezel Kit



iM2600-BEZEL
Base Bezel Kit



iM2600-FOAM
5 pc. Replacement Foam Set



iM-STRAP-S-VER2
Padded Shoulder Strap



iM-LIDSTAY
Lid Stay



iM2600TPKIT
TrekPak Case Divider Kit



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 06-02-26