



9415

9410L + SAFETY = 9415

Everything that's great about the 9410L LED Lantern, plus safety certifications. At just 3 pounds and 588* lumens, the new 9415 LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 314 yards (288* meters). And it's loaded with innovative technology and features you have come to expect from Pelican. Whether you're on a USAR team or the 3rd shift at a refinery, you'll appreciate the compact size and high output of the new 9415 LED Lantern.

Safety approved for the most volatile work areas, the 9415 LED Lantern is safe and one of the most compact, high output lanterns on the market.

9415 LED Lantern: Lightweight, big LED performance you can trust.

*Performance data is to FL 1 standards

- Built Pelican tough
- Handy push button on/off switch
- High/Low/Flashing Modes
- Super bright LED beam
- Safety Certified - Class I, Division I
- Approved to NFPA (National Fire Protection Association) 1901
- Carrying Strap included



DIMENSIONS

Length	8.75" (22.2 cm)
---------------	-----------------

MATERIALS

Body	ABS
O-Ring	EPDM
Lens	Polycarbonate (PC)
Shroud	EXL

COLOURS

High Visibility Yellow

LIGHT SPECS

Lamp Type	LED
------------------	-----

POWER

Battery Type	NiMH
Battery Quantity	4
Batteries Included	yes
Rechargeable	yes
Charge Time	15 hrs
Battery Level Indicator	RGB LED
Volts	4.8v

WEIGHT

Weight With Batteries 49.3 oz (1398 gr)
Weight Without Batteries 0.0 oz (0 gr)

SWITCH

Switch Type Push Button
Light Modes High / Low / Flashing

CERTIFICATIONS

Class I, Division 1

OTHER

Minimum Pack 1
Package Code B

FL1 STANDARD	HIGH	LOW
	588 LUMENS	224 LUMENS
	4h 30mins	11h 30mins
	288m	176m
	20792cd	7787cd
	IPX4	

ACCESSORIES



9416
Deck/Dash Charger Base Unit



6061F
Direct Wiring Rig for Fast Charger



8056F
12v Plug-in for Fast Charger



9418
Replacement Battery

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 02-02-26