



1200 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Ultra-tough HPX^P Polymer Construction



CONFIGURATIONS



1200
Standard



1200WF
With Foam



1200NF
No Foam

DIMENSIONS

Interior (LxWxD)	9.31 x 7.13" x 4.12 (23.6 x 18.1 x 10.5 cm)
Exterior (LxWxD)	10.67 x 9.75" x 4.86 (27.1 x 24.8 x 12.3 cm)
Lid Depth	1.19" (3 cm)
Bottom Depth	2.93" (7.4 cm)
Total Depth	4.12" (10.5 cm)
Int Volume	0.16 ft ³ (0.005 m ³)
Padlock Hole Diameter	0.19" (0.5 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	EDPM Medium Density
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	LM10411

COLOURS

 Black	 Desert Tan	 Orange	 OD Green
---	--	--	--

■ Silver

■ Yellow

WEIGHT

Weight With Foam	2.75 lbs (1.25 kg)
Weight Empty	2.55 lbs (1.16 kg)
Buoyancy	13.80 lbs (6.26 kg)
Master Pack Weight	19.00 lbs (8.62 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

OTHER

Master Pack	6
Military	yes

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 04-05-26