1560
Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.
Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.



- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Ultra-tough HPX^{p} Polymer Construction

CONFIGURATIONS



1560
Standard



1564
With Padded Dividers



1560NF
No Foam



1560TP
With TrekPak Divider System



1560WF
With Foam

1560TPL
TrekPak Divider System with Mesh Lid Organizer

1560PDL
Padded Dividers with Mesh Lid Organizer



1560PB
With Foam / Push Button Latch

DIMENSIONS

Interior (L×W×D)	19.92 x 14.98" x 9.00 (50.6 x 38 x 22.9 cm)
Exterior (L×W×D)	22.07 x 17.92" x 10.42 (56.1 x 45.5 x 26.5 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	7.00" (17.8 cm)
Total Depth	9" (22.9 cm)
Int Volume	1.55 ft³ (0.044 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

Black, Desert Tan, Orange, OD Green, Yellow

WEIGHT

Weight With Foam	20.00 lbs (9.07 kg)
Weight Empty	17.00 lbs (7.71 kg)
Buoyancy	115.00 lbs (52.16 kg)
Master Pack Weight	21.00 lbs (9.53 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Wheels	2
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Military	yes


ACCESSORIES



0343
Replacement O-ring



1561
4 pc. Replacement Foam Set



1562
Pick N Pluck™ Sections Only (set of 2)



1565
Padded Divider Set



1569
Lid Organizer



1560TPKIT
TrekPak Case Divider Kit



1507QM
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1560MP
EZ-Click™ MOLLE Panel

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 11-04-26