



# 1650 Protector

The original case introduced over 45 years ago has since evolved into the global standard for equipment protection. The Protector Case series is designed to survive and trusted to travel to the harshest environments on earth.

The Pelican 1650 Protector Case provides military-grade protection for a wide variety of gear, from camera equipment to camping kits. It is available with foam, without foam, padded dividers, or TrekPak dividers.

- Personalized nameplate service available
- **4 strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Ultra-tough HPX<sup>P</sup> Polymer Construction



## CONFIGURATIONS



**1650**  
Standard



**1654**  
With Padded Dividers



**1650NF**  
No Foam



**1650TP**  
With TrekPak Divider System



**1650WF**  
With Foam

## DIMENSIONS

<b>Interior (L×W×D)</b>	28.57 x 17.52" x 10.65 (72.6 x 44.5 x 27.1 cm)
<b>Exterior (L×W×D)</b>	31.59 x 20.47" x 12.45 (80.2 x 52 x 31.6 cm)
<b>Lid Depth</b>	1.81" (4.6 cm)
<b>Bottom Depth</b>	8.84" (22.5 cm)
<b>Total Depth</b>	10.65" (27.1 cm)
<b>Int Volume</b>	3.08 ft <sup>3</sup> (0.087 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.31" (0.8 cm)

## MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane

**Purge Body** ABS  
**Purge Vent** 3 Micron Hydrophobic Non-Woven

## COLOURS

Black
  Desert Tan
  OD Green

## WEIGHT

**Weight With Foam** 28.06 lbs (12.73 kg)  
**Weight Empty** 24.03 lbs (10.9 kg)  
**Buoyancy** 181.00 lbs (82.1 kg)  
**Master Pack Weight** 30.10 lbs (13.65 kg)

## TEMPERATURE

**Minimum Temperature** -40°F (-40 °C)  
**Maximum Temperature** 190°F (87.8 °C)

## CERTIFICATIONS

**IP67**  
**MIL C-4150J**  
**Def Stan 81-41**  
**ATA 300**

## OTHER

**Wheels** 4  
**Extendable Handle** yes  
**Master Pack** 1  
**Nameplate** yes  
**Reduced Area** yes  
**Military** yes

## ACCESSORIES



**1651**  
4 pc. Replacement Foam Set



**1652**  
Pick N Pluck™ Sections Only  
(set of 2)



**1653**  
Replacement O-ring



**1655**  
Padded Divider Set



**1659**  
Photo/Lid Organizer




**1650TPKIT**  
TrekPak Case Divider Kit




**1507QM**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**1650MP**  
EZ-Click™ MOLLE Panel

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 06-12-26*