



## 472-PWC-MP5

### Mobile Armory™

#### Machine Gun Case

Injection molded Pelican™ Storm Case™ with HPX resin plastic body case with polyethylene foam cushion designed to fit (1) MP5 (with or without suppressor). Unique foam cavities easily accommodates dual magazines, shoulder harness, slings, and cleaning kits.

Airtight / Watertight case features automatic pressure equalization valve, (6) hinged push-button latches, (2) padlockable hasps, (1) padded handle, (1) extra wide padded handle with recessed inline wheels and waterproof O-ring gasket. Meets airline luggage regulations.

Full lifetime warranty against defects in material or workmanship, and breakage.



#### DIMENSIONS

|                         |                                               |
|-------------------------|-----------------------------------------------|
| <b>Interior (LxWxD)</b> | 36.50 x 14.00" x 6.00 (92.7 x 35.6 x 15.2 cm) |
| <b>Exterior (LxWxD)</b> | 39.80 x 16.50" x 6.70 (101.1 x 41.9 x 17 cm)  |
| <b>Lid Depth</b>        | 2.00" (5.1 cm)                                |
| <b>Bottom Depth</b>     | 4.00" (10.2 cm)                               |
| <b>Total Depth</b>      | 6" (15.2 cm)                                  |
| <b>Int Volume</b>       | 1.77 ft³ (0.05 m³)                            |

#### MATERIALS

|                         |                                              |
|-------------------------|----------------------------------------------|
| <b>Body</b>             | Injection Molded HPX™ high performance resin |
| <b>Latch</b>            | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Latch (Alt)</b>      | Xenoy - Polyester/Polycarbonate blend        |
| <b>O-Ring</b>           | Silicone Sponge                              |
| <b>Pins</b>             | Stainless Steel                              |
| <b>Foam</b>             | 1.3/1.35 polyester                           |
| <b>Purge Body</b>       | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Body (Alt)</b> | Xenoy - Polyester/Polycarbonate blend        |
| <b>Purge Vent</b>       | Gortex membrane                              |

#### COLOURS

|                                                                                           |                                                                                              |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
|  Black |  OD Green |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|

#### WEIGHT

|               |                     |
|---------------|---------------------|
| <b>Weight</b> | 19.80 lbs (8.98 kg) |
|---------------|---------------------|

#### TEMPERATURE

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -20°F (-28.9 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)    |

OTHER

---

|               |   |
|---------------|---|
| <b>Wheels</b> | 2 |
|---------------|---|

---

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 02-02-26*