



1930Z0

L1™

Same features as L1™ 1930 LED with static-dissipation materials body. Being certified to ATEX safe for use in high-risk hazardous locations, Zone 0 (Category 1) areas, L1™ 1930Z0 LED is ideal for professionals who work in chemical, pharmaceutical, power, oil and gas, and fire rescue industries.



DIMENSIONS

| | |
|---------------|----------------|
| Length | 2.64" (6.7 cm) |
|---------------|----------------|

MATERIALS

| | |
|--------------------------------|------------------------------------|
| Body | Anti-static Impact Modified PC/PBT |
| O-Ring | Ethylene Propylene |
| Lens | Polycarbonate (PC) |
| Shroud | Anti-static Impact Modified PC/PBT |
| Contact Spring Retainer | Phosphore Bronze |

COLOURS

| | |
|---|------|
| | Gray |
|---|------|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|---------------------------|----------|
| Battery Size | LR 44 |
| Battery Type | Alkaline |
| Battery Quantity | 4 |
| Batteries Included | yes |
| Volts | 6.0v |

WEIGHT

| | |
|---------------------------------|----------------|
| Weight With Batteries | 0.9 oz (26 gr) |
| Weight Without Batteries | 0.6 oz (17 gr) |
| Packaged Weight | 0.8 oz (23 gr) |

SWITCH

| | |
|--------------------|------------------|
| Switch Type | Push Button Tail |
| Light Modes | On / Off |

CERTIFICATIONS

ATEX Zone 0

OTHER

| | |
|--------------|-----|
| Minimum Pack | 12 |
| Military | yes |
| Package Code | C |

| FL1 STANDARD | HIGH |
|---|-----------|
|  | 12 LUMENS |
|  | 4h 15mins |
|  | 17m |
|  | 70cd |
|  | IPX4 |

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 01-31-26