



AL2624-1805

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

- Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact
- Reinforced corners and edges for additional impact protection
- Molded-in ribs and corrugations for secure, non-slip stacking, columnar strength, and added protection
- Recessed hardware for extra protection
- Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware
- Patented molded-in metal inserts for catch and hinge attachment points, which provide strength and spread loads to the container
- One-piece construction, molded from lightweight, high-impact polyethylene



CONFIGURATIONS



AL2624-1805
Standard



AL2624-1805-RP
Empty



AL2624-1805RPC
No Foam, With Casters



AL2624-1805RPFC
With Foam, With Casters

DIMENSIONS

Interior (L×W×D)	26.06 x 24.00" x 22.87 (66.2 x 61 x 58.1 cm)
Exterior (L×W×D)	29.06 x 27.00" x 26.62 (73.8 x 68.6 x 67.6 cm)
Lid Depth	5.06" (12.9 cm)
Bottom Depth	17.81" (45.2 cm)
Total Depth	22.87" (58.1 cm)
Int Volume	8.28 ft ³ (0.234 m ³)

MATERIALS

Body	RotoMolded Polyethylene
Latch	Steel (Nickel-black Plated)
O-Ring	Silicone Sponge
Foam	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined
Purge Body	Aluminum
Handle	Heavy Duty Injection Molded Standard
Hardware	Yellow Carbon Steel Standard

COLOURS

 Gray - 133 Fed Std
26270

WEIGHT

Weight 38.50 lbs (17.5 kg)
Buoyancy 716.13 lbs (324.8 kg)
Master Pack Weight 40.50 lbs (18.4 kg)

TEMPERATURE

Minimum Temperature -20°F (-28.9 °C)
Maximum Temperature 140°F (60 °C)

OTHER

Military yes

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 08-27-25