



# 1060

## Micro

The Peli 1060 Micro Case is perfect for protecting small electronic devices and other valuables when you're on the road. This small protective case comes with a handy carabiner clip, clip closure on the front of the case, automatic purge valve and a rubber liner that provides protection and also acts as a sealing gasket. The case is waterproof, dustproof and shockproof.

- **\*Case is able to be submerged under 1 meter of water for up to 30 minutes in accordance with IP67 testing parameters**
- **Available in clear with color liner or solid**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Carabiner
- Easy open latch
- Rubber liner for extra protection doubles as o-ring seal
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



## DIMENSIONS

<b>Interior (L×W×D)</b>	8.25 x 4.25" x 2.25 (21 x 10.8 x 5.7 cm)
<b>Exterior (L×W×D)</b>	9.88 x 5.59" x 2.63 (25.1 x 14.2 x 6.7 cm)
<b>Lid Depth</b>	0.69" (1.8 cm)
<b>Bottom Depth</b>	1.44" (3.7 cm)
<b>Total Depth</b>	2.13" (5.4 cm)
<b>Int Volume</b>	0.05 ft³ (0.001 m³)

## MATERIALS

<b>Body</b>	Polycarbonate (PC)
<b>Latch</b>	Xylex
<b>O-Ring</b>	Thermoplastic Rubber
<b>Pins</b>	Stainless Steel
<b>Foam</b>	TL - 426 4 lb. Esther
<b>Purge Body</b>	Polycarbonate (PC)
<b>Purge Vent</b>	Polyester Spun-Bond ePTFE Oleophobic

## COLOURS

■ Black	■ Blue	■ Red	■ Yellow
■ Black - Clear	■ Yellow - Clear		

## WEIGHT

<b>Weight With Foam</b>	1.03 lbs (0.5 kg)
<b>Weight Empty</b>	1.00 lbs (0.5 kg)
<b>Buoyancy</b>	2.49 lbs (1.1 kg)
<b>Master Pack Weight</b>	7.08 lbs (3.2 kg)

TEMPERATURE

---

**Minimum Temperature**    -10°F (-23.3 °C)  
**Maximum Temperature**    199°F (92.8 °C)

CERTIFICATIONS

---

**IP67**

OTHER

---

**Minimum Pack**                6  
**Master Pack**                6  
**Military**                      yes

ACCESSORIES

---



**1062**  
Pick N Pluck™ Foam Insert

---

**Peli**  
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 09-15-25*