

# 1556 Air

Peli understands that finding the right protection, with the perfect fit for your gear, is a priority. Peli<sup>™</sup> Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Peli's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Peli's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Peli has you covered.

• Automatic pressure equalization valve - balances interior pressure, keeps water out

- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- Maximum airline carry-on size\*
- Press and Pull<sup>™</sup> Latches
  Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2™</sup> Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck<sup>™</sup> foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified

## CONFIGURATIONS



1556 Standard



1556WF With Foam



1556NF No Foam

#### DIMENSIONS

Interior (L×W×D)	21.63 x 10.76" x 8.97 (54.9 x 27.3 x 22.8 cm)
Exterior (L×W×D)	23.43 x 13.52" x 10.57 (59.5 x 34.3 x 26.8 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	6.97" (17.7 cm)
Total Depth	8.97" (22.8 cm)
Int Volume	1.21 ft <sup>3</sup> (0.034 m <sup>3</sup> )
Padlock Hole Diameter	0.31" (0.8 cm)

#### MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM

Purge Body Purge Vent ABS Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

# COLOURS

Black

# WEIGHT

Weight With Foam	11.20 lbs (5.1 kg)
Weight Empty	9.75 lbs (4.4 kg)
Buoyancy	84.95 lbs (38.5 kg)

### TEMPERATURE

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)

# ACCESSORIES



1556AirFS

7 pc. Replacement Foam Set



1506TSA

TSA Lock

RucPac-Pro-1 RucPac Pro Hardcase Backpack Conversion

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 09-15-25