SUPER-V-SERIES-3U

Super V

3U

• Fixed square hole frame for universal equipment fit
• 2” Front Lid, 5” Rear Lid
• Anti-reflective black hardware
• Coupling catches for secure stacking
• Molded in rear edge casters with handles on the lid for ease of movement
• Comfort Grip plastic handles
• High-strength steel rack frame supports equipment from 10 - 50 kg
• Designed to meet the requirements of Def Stan 81-41 Level J, Mil Standard 810, STANAG 4340 and other European standards.
• Designed to meet ANSI/EIA-310-C for universal rack mounting hole pattern
• 10 different models, frame heights 4-12U in two depths, 480 and 610mm
• Metric M6 clip nuts for more flexibility in mounting equipment
• Lid hangers for lid storage while in use
• Sealed gasket and PRV keeps container watertight and eliminates over pressurization
• REACH and RoHs compliant



DIMENSIONS

Exterior (L×W×D)	38.50 x 28.30" x 11.40 (97.8 x 71.9 x 29 cm)
Rack Height	5.25" (13.3 cm)
Rack Depth	24.00" (61 cm)
Interior Lid Depth	2.20" (5.6 cm)
Interior Back Lid Depth	5.20" (13.2 cm)

MATERIALS

Body	RotoMolded Polyethylene
O-Ring	Silicone Sponge
Purge Body	Aluminum
Hardware	Stainless Steel (Black Oxide) / RoHs Nickel Black
Frame	Steel (Clear Coated)

COLOURS

Black

WEIGHT

Weight 50.00 lbs (22.68 kg)

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 11-17-26