



1430

Protector

Top Loader Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Unique top loading design**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Optional shoulder strap available
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1430
Standard



1434
With Padded Dividers & Lid Organizer



1437
With Padded Office Divider Set & Lid Organizer



1430NF
No Foam



1430WF
With Foam

DIMENSIONS

Interior (LxWxD)	13.56 x 5.76" x 11.70 (34.4 x 14.6 x 29.7 cm)
Exterior (LxWxD)	16.40 x 8.71" x 13.15 (41.7 x 22.1 x 33.4 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	9.70" (24.6 cm)
Total Depth	11.7" (29.7 cm)
Int Volume	0.53 ft ³ (0.015 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS

Purge Vent

3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

■ Desert Tan

■ Orange

■ Yellow

WEIGHT

Weight With Foam	6.50 lbs (2.95 kg)
Weight Empty	5.60 lbs (2.54 kg)
Buoyancy	59.00 lbs (26.76 kg)
Master Pack Weight	8.09 lbs (3.67 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

Master Pack	1
Nameplate	yes
Military	yes

ACCESSORIES



1431
5 pc. Replacement Foam Set



1432
Strap Kit



1433
Replacement O-ring



1435
Padded Divider Set



1436
Office Divider Kit




1439
Lid Organizer



1430PF
Special Application Panel
Frame



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-16-26