



1555

Air

Peli™ Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 45 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started. With the launch of the Peli™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX2™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



CONFIGURATIONS



1555
Standard

1555NF
No Foam

1555WD
With Padded Dividers

1555TP
With TrekPak Divider System

1555WF
With Foam

DIMENSIONS

Interior (LxWxD)	23.00 x 12.75" x 7.50 (58.4 x 32.4 x 19.1 cm)
Exterior (LxWxD)	24.76 x 15.46" x 8.24 (62.9 x 39.3 x 20.9 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	5.50" (14 cm)
Total Depth	7.5" (19.1 cm)
Int Volume	1.27 ft ³ (0.036 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

- Black
- Orange
- Yellow

WEIGHT

Weight With Foam	9.02 lbs (4.09 kg)
Weight Empty	7.37 lbs (3.34 kg)
Buoyancy	81.20 lbs (36.83 kg)

TEMPERATURE

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)

ACCESSORIES




1555AirFS
4 pc. Replacement Foam Set



1555AirDS
Padded Divider Set



1555TP-KIT
TrekPak Case Divider Kit



1555TPKIT
TrekPak Case Divider Kit



1555TPDIV
Extra TrekPak Dividers



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



RucPac-Pro-1
RucPac Pro Hardcase
Backpack Conversion

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-16-26