



472-PWC-FIRES

Per Dispositivi Medici

SCBA FIRES System Case

This Peli™ iM2950 case securely transports an SCBA system with space to store three replacement filters. This watertight & crushproof case features a hinged lid, five Press & Pull™ latches, two double-layered soft grip handle, two padlock-able hasps, a Vortex™ valve and comes with a lifetime guarantee.

- Custom interior designed to hold a harness with cylinder attached, regulator and pressure gauge
- Included strap secures the mask
- Room to store up to three extra filters



DIMENSIONI

| | |
|-----------------------------|--|
| INTERNO | 29.00 x 18.00" x 10.50 (73.7 x 45.7 x 26.7 cm) |
| ESTERNO | 31.30 x 20.40" x 12.20 (79.5 x 51.8 x 31 cm) |
| profondità coperchio | 2.00" (5.1 cm) |
| profondità fondo | 8.50" (21.6 cm) |
| profondità totale | 10.5" (26.7 cm) |
| Volume interno | 3.17 ft ³ (0.09 m ³) |

MATERIALE

| | |
|--|--|
| Corpo | Injection Molded HPX™ high performance resin |
| Fermo | Valox - Polybutylene Terephthalate (PBT) |
| Fermo (Alt) | Xenoy - Polyester/Polycarbonate blend |
| o-ring | EPDM |
| Perni | Stainless Steel |
| schiuma | Aluminum |
| gruppo di regolazione pressione | 1.3/1.35 polyester |
| Gruppo di regolazione pressione (Alt) | Valox - Polybutylene Terephthalate (PBT) |
| valvola di sfianto | Xenoy - Polyester/Polycarbonate blend |

COLORI

| | |
|---------|------------|
| ■ Black | ■ OD Green |
|---------|------------|

TEMPERATURA

| | |
|----------------------------|------------------|
| temperatura minima | -20°F (-28.9 °C) |
| temperatura massima | 140°F (60 °C) |

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 06-13-26