



## AL2624-1805

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

- Linee di divisione moldate e dotate di guarnizione per garantire la massima resistenza agli schizzi e una tenuta ermetica anche
- Spigoli e bordi rinforzati per una maggiore protezione contro gli urti
- Costole di rinforzo, stampate e sagomate, per mantenere il contenitore stabile, in posizione verticale
- Struttura a scanalature per un'ulteriore protezione
- Chiusure anti-cesoiamento che impediscono il distacco del coperchio in caso di impatto e riducono lo stress
- Inserti in metallo moldati brevettati per offrire punti di attacco a innesto e cerniera
- Struttura in un unico pezzo, stampata in polietilene leggero e ultrasensibile agli urti




### CONFIGURAZIONI



**AL2624-1805**  
Standard



**AL2624-1805-RP**  
Empty



**AL2624-1805RPC**  
No Foam, With Casters



**AL2624-1805RPFC**  
With Foam, With Casters

### DIMENSIONI

<b>INTERNO</b>	26.06 x 24.00" x 22.87 (66.2 x 61 x 58.1 cm)
<b>ESTERNO</b>	29.06 x 27.00" x 26.62 (73.8 x 68.6 x 67.6 cm)
<b>profondità coperchio</b>	5.06" (12.9 cm)
<b>profondità fondo</b>	17.81" (45.2 cm)
<b>profondità totale</b>	22.87" (58.1 cm)
<b>Volume interno</b>	8.28 ft <sup>3</sup> (0.234 m <sup>3</sup> )

### MATERIALE

<b>Corpo</b>	RotoMolded Polyethylene
<b>Fermo</b>	Steel (Nickel-black Plated)
<b>o-ring</b>	Silicone Sponge
<b>schiuma</b>	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined
<b>gruppo di regolazione pressione</b>	Aluminum
<b>maniglia</b>	Heavy Duty Injection Molded Standard
<b>bulloneria</b>	Yellow Carbon Steel Standard

## COLORI

---

■ Gray - 133 Fed Std  
26270

## IL PESO

---

**Peso** 38.50 lbs (17.46 kg)  
**flottabilità** 716.13 lbs (324.83 kg)  
**Master Pack Weight** 40.50 lbs (18.37 kg)

## TEMPERATURA

---

**temperatura minima** -20°F (-28.9 °C)  
**temperatura massima** 140°F (60 °C)

## ALTRO

---

**Militare** sì

---

### **Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 06-17-26*