AL2624-1805

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

• Linee di divisione moldate e dotate di guarnizione per garantire la massima resistenza agli schizzi e una tenuta ermetica anche
• Spigoli e bordi rinforzati per una maggiore protezione contro gli urti
• Costole di rinforzo, stampate e sagomate, per mantenere il contenitore stabile, in posizione verticale
• Struttura a scanalature per un'ulteriore protezione
• Chiusure anti-cesoiamento che impediscono il distacco del coperchio in caso di impatto e riducono lo stress
• Inserti in metallo moldati brevettati per offrire punti di attacco a innesto e cerniera
• Struttura in un unico pezzo, stampata in polietilene leggero e ultraresistente agli urti

CONFIGURAZIONI

AL2624-1805
Standard

AL2624-1805-RP
Empty

AL2624-1805RPC
No Foam, With Casters

AL2624-1805RPFC
With Foam, With Casters

DIMENSIONI

INTERNO	26.06 x 24.00" x 22.87 (66.2 x 61 x 58.1 cm)
ESTERNO	29.06 x 27.00" x 26.62 (73.8 x 68.6 x 67.6 cm)
profondità coperchio	5.06" (12.9 cm)
profondità fondo	17.81" (45.2 cm)
profondità totale	22.87" (58.1 cm)
Volume interno	8.28 ft³ (0.234 m³)

MATERIALE

Corpo	RotoMolded Polyethylene
Fermo	Steel (Nickel-black Plated)
o-ring	Silicone Sponge
schiuma	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined
gruppo di regolazione pressione	Aluminum
maniglia	Heavy Duty Injection Molded Standard

bulloneria	Yellow Carbon Steel Standard

COLORI

Gray - 133 Fed Std 26270

IL PESO

Peso	38.50 lbs (17.46 kg)
flottabilità	716.13 lbs (324.83 kg)
Master Pack Weight	40.50 lbs (18.37 kg)

TEMPERATURA

temperatura minima	-20°F (-28.9 °C)
temperatura massima	140°F (60 °C)

ALTRO

Militare	sì

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 10-14-26