



1605

Air

Pelican™ Air cases are the first in a series of remarkable innovations engineered by Pelican, the pioneers of protective cases. For over 45 years Pelican has designed and crafted the most influential protective cases in the world, and we're just getting started. With the launch of the Pelican™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- Made in the USA



CONFIGURATIONS



1605
Standard



1605NF
No Foam



1605WD
With Padded Dividers



1605TP
With TrekPak Divider System



1605WF
With Foam

DIMENSIONS

Interior (L×W×D)	26.00 x 14.00" x 8.38 (66 x 35.6 x 21.3 cm)
Exterior (L×W×D)	28.87 x 16.77" x 9.12 (73.3 x 42.6 x 23.2 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	6.38" (16.2 cm)
Total Depth	8.38" (21.3 cm)
Int Volume	1.77 ft ³ (0.05 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLORS

 Black	 Orange	 Silver	 Yellow
---	--	--	--

WEIGHT

Weight With Foam	11.61 lbs (5.27 kg)
Weight Empty	9.28 lbs (4.21 kg)
Buoyancy	112.90 lbs (51.21 kg)

TEMPERATURE

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)

ACCESSORIES

				
1605AirFS 4 pc. Replacement Foam Set	1605AirDS Padded Divider Set	1605TPKIT TrekPak Case Divider Kit	1605TPDIV Extra TrekPak Dividers	1506TSA TSA Lock
				
1500D Desiccant Silica Gel				

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 02-01-26