



1060

Micro

The Pelican 1060 Micro Case is perfect for protecting small electronic devices and other valuables when you're on the road. This small protective case comes with a handy carabiner clip, clip closure on the front of the case, automatic purge valve and a rubber liner that provides protection and also acts as a sealing gasket. The case is waterproof, dustproof and shockproof.

- ***Case is able to be submerged under 1 meter of water for up to 30 minutes in accordance with IP67 testing parameters**
- **Available in clear with color liner or solid**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Carabiner
- Easy open latch
- Lifetime Guarantee of Excellence
- Rubber liner for extra protection doubles as o-ring seal
- Stainless steel hardware










DIMENSIONS

Interior (LxWxD)	8.25 x 4.25" x 2.25 (21 x 10.8 x 5.7 cm)
Exterior (LxWxD)	9.88 x 5.59" x 2.63 (25.1 x 14.2 x 6.7 cm)
Lid Depth	0.69" (1.8 cm)
Bottom Depth	1.44" (3.7 cm)
Total Depth	2.13" (5.4 cm)
Int Volume	0.05 ft ³ (0.001 m ³)

MATERIALS

Body	Polycarbonate (PC)
Latch	Xylex
O-Ring	Thermoplastic Rubber
Pins	Stainless Steel
Foam	TL - 426 4 lb. Esther
Purge Body	Polycarbonate (PC)
Purge Vent	Polyester Spun-Bond ePTFE Oleophobic

COLORS

 Black	 OD Green	 Yellow	 Tan
 Seafoam	 Black - Clear	 Yellow - Clear	 Blue - Clear
 Red - Clear	 Bright Green		

WEIGHT

Weight With Foam	1.03 lbs (0.47 kg)
Weight Empty	1.00 lbs (0.45 kg)
Buoyancy	2.49 lbs (1.13 kg)
Master Pack Weight	7.08 lbs (3.21 kg)

TEMPERATURE

Minimum Temperature -10°F (-23.3 °C)
Maximum Temperature 199°F (92.8 °C)

CERTIFICATIONS

IP67

OTHER

Minimum Pack 6
Master Pack 6
Military yes

ACCESSORIES



1061
Replacement Case Liner



1062
Pick N Pluck™ Foam Insert

Pelican
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 02-01-26