



## V730

### Vault

Tactical Rifle Case

Built for hard use, high impact and supreme weather resistance, new Vault series gun cases are the most rugged and secure in their class. Equipped with a host of premium protective features at a price more hunters and shooters can afford, as only the 42-year veteran of hard knocks could deliver.

- Four layers of protective foam
- Made in the USA
- Crushproof, dustproof, and weather-resistant
- High-impact polymer assures protection of your firearm, via road, trail or air
- Heavy duty handles are ergonomic and will stand up in even the toughest conditions
- Six push button latches offer secure closure with easy-open access
- Ideally suited for today's tactical firearms and their accessories



### DIMENSIONS

<b>Interior (LxWxD)</b>	44.00 x 16.00" x 6.25 (111.8 x 40.6 x 15.9 cm)
<b>Exterior (LxWxD)</b>	47.12 x 19.18" x 6.90 (119.7 x 48.7 x 17.5 cm)
<b>Lid Depth</b>	1.57" (4 cm)
<b>Bottom Depth</b>	4.68" (11.9 cm)
<b>Total Depth</b>	6.25" (15.9 cm)
<b>Int Volume</b>	2.55 ft <sup>3</sup> (0.072 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.46" (1.2 cm)

### MATERIALS

<b>Body</b>	Polyethylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.12 lbs. ELE (Polyurethane)
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

### COLORS

Black

Tan

Ghost Gray

### WEIGHT

<b>Weight With Foam</b>	22.07 lbs (10.01 kg)
<b>Weight Empty</b>	17.30 lbs (7.85 kg)
<b>Master Pack Weight</b>	25.00 lbs (11.34 kg)

### TEMPERATURE

<b>Minimum Temperature</b>	0°F (-17.8 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

## OTHER

---

### Wheels

2

## ACCESSORIES

---



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**V730FS**  
4 pc. Replacement Foam Set



**LGMT-001P**  
Protector Case Roof Mount

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 02-01-26*