



## SUPER-V-SERIES-3U

### Super V 3U

- Fixed square hole frame for universal equipment fit
- 2" Front Lid, 5" Rear Lid
- Anti-reflective black hardware
- Coupling catches for secure stacking
- Choice of SAE 10-32 or Metric M6 clip nuts for even more flexibility in mounting equipment
- Molded in rear edge casters with handles on the lid for ease of movement
- Comfort Grip plastic handles
- High-strength steel rack frame supports equipment from 10 - 50 kg
- Designed to meet the requirements of Def Stan 81-41 Level J, Mil Standard 810, STANAG 4340 and other European standards.
- Designed to meet ANSI/EIA-310-C for universal rack mounting hole pattern
- 10 different models, frame heights 4-12U in two depths, 480 and 610mm
- Lid hangers for lid storage while in use
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- REACH and RoHs compliant



### DIMENSIONS

|                                |                                              |
|--------------------------------|----------------------------------------------|
| <b>Exterior (LxWxD)</b>        | 38.50 x 28.30" x 11.40 (97.8 x 71.9 x 29 cm) |
| <b>Rack Height</b>             | 5.25" (13.3 cm)                              |
| <b>Rack Depth</b>              | 24.00" (61 cm)                               |
| <b>Interior Lid Depth</b>      | 2.20" (5.6 cm)                               |
| <b>Interior Back Lid Depth</b> | 5.20" (13.2 cm)                              |

### MATERIALS

|                   |                                                   |
|-------------------|---------------------------------------------------|
| <b>Body</b>       | RotoMolded Polyethylene                           |
| <b>O-Ring</b>     | Silicone Sponge                                   |
| <b>Purge Body</b> | Aluminum                                          |
| <b>Hardware</b>   | Stainless Steel (Black Oxide) / RoHs Nickel Black |
| <b>Frame</b>      | Steel (Clear Coated)                              |

### COLORS

■ Black

### WEIGHT

|               |                      |
|---------------|----------------------|
| <b>Weight</b> | 50.00 lbs (22.68 kg) |
|---------------|----------------------|

#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

