



## 1200 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.



### CONFIGURATIONS



**1200**  
Standard



**1200WF**  
With Foam



**1200NF**  
No Foam

### DIMENSIONS

<b>Interior (LxWxD)</b>	9.31 x 7.13" x 4.12 (23.6 x 18.1 x 10.5 cm)
<b>Exterior (LxWxD)</b>	10.67 x 9.75" x 4.86 (27.1 x 24.8 x 12.3 cm)
<b>Lid Depth</b>	1.19" (3 cm)
<b>Bottom Depth</b>	2.93" (7.4 cm)
<b>Total Depth</b>	4.12" (10.5 cm)
<b>Int Volume</b>	0.16 ft <sup>3</sup> (0.005 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.19" (0.5 cm)

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	EDPM Medium Density
<b>Pins</b>	Stainless Steel
<b>Foam</b>	Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	LM10411

## COLORS

---

Black  
Silver

Desert Tan  
Yellow

Orange

OD Green

## WEIGHT

---

<b>Weight With Foam</b>	2.75 lbs (1.25 kg)
<b>Weight Empty</b>	2.55 lbs (1.16 kg)
<b>Buoyancy</b>	13.80 lbs (6.26 kg)
<b>Master Pack Weight</b>	19.00 lbs (8.62 kg)

## TEMPERATURE

---

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	190°F (87.8 °C)

## OTHER

---

<b>Master Pack</b>	6
<b>Military</b>	yes

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 02-01-26*