



1300 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.



CONFIGURATIONS



1300
Standard



1300WF
With Foam



1300NF
No Foam

DIMENSIONS

Interior (L×W×D)	9.17 x 6.99" x 6.15 (23.3 x 17.8 x 15.6 cm)
Exterior (L×W×D)	10.70 x 9.76" x 6.89 (27.2 x 24.8 x 17.5 cm)
Lid Depth	1.19" (3 cm)
Bottom Depth	4.96" (12.6 cm)
Total Depth	6.15" (15.6 cm)
Int Volume	0.23 ft ³ (0.007 m ³)
Padlock Hole Diameter	0.19" (0.5 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	EDPM Medium Density
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	LM10411

COLORS

Black
 Yellow

Orange

OD Green

Silver

WEIGHT

Pelican

Weight With Foam	3.30 lbs (1.5 kg) 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com	
Weight Empty	3.10 lbs (1.41 kg)	
Buoyancy	18.50 lbs (8.39 kg) <i>Document created on 02-01-26</i>	
Master Pack Weight	17.00 lbs (7.71 kg)	

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

OTHER

Master Pack	4
Military	yes

ACCESSORIES