



## 1930

### L1™

With a long lamp life and extended battery burn time, you won't be left in the dark with the L1™ flashlight. The polycarbonate body is resistant to chemicals, water and corrosion. The convenient tail switch for constant on/momentary is easy to operate. The L1™ is perfect for close quarter use. Packaged with 4 LR 44 1.5V alkaline coin cells, a break-a-way safety lanyard, and colored lens discs to preserve night vision. This handy flashlight offers a lot for its size.


- Built Pelican tough
- Super bright LED beam
- Unconditional Lifetime Guarantee of Excellence
- Security Lanyard



## CONFIGURATIONS



**1930**  
Standard



**1930M**  
Merchandiser Display

## DIMENSIONS

<b>Length</b>	2.64" (6.7 cm)
---------------	----------------

## MATERIALS

<b>Body</b>	Polycarbonate (PC)
<b>O-Ring</b>	Ethylene Propylene
<b>Lens</b>	Polycarbonate (PC)
<b>Shroud</b>	Xenoy
<b>Contact Spring Retainer</b>	Phosphore Bronze

## COLORS

<span style="background-color: black; width: 10px; height: 10px; display: inline-block;"></span> Black	<span style="background-color: yellow; width: 10px; height: 10px; display: inline-block;"></span> High Visibility Yellow
--	--

## LIGHT SPECS

<b>Lamp Type</b>	LED
------------------	-----

## POWER

<b>Battery Size</b>	LR 44
---------------------	-------

---

<b>Battery Type</b>	Alkaline
<b>Battery Quantity</b>	4
<b>Batteries Included</b>	yes
<b>Volts</b>	6.0v

## WEIGHT

---

<b>Weight With Batteries</b>	0.9 oz (26 gr)
<b>Weight Without Batteries</b>	0.6 oz (17 gr)
<b>Packaged Weight</b>	0.8 oz (23 gr)

## SWITCH

---

<b>Switch Type</b>	Push Button Tail
<b>Light Modes</b>	On / Off

## CERTIFICATIONS


---

**Class I, Division 1**

## OTHER

---

<b>Minimum Pack</b>	12
<b>Military</b>	yes
<b>Package Code</b>	C

FL1 STANDARD	HIGH
	12 LUMENS
	4h 15mins
	17m
	70cd
	IPX4

## ACCESSORIES

**Pelican**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

*Document created on 02-02-26*