iM2400

Storm

Laptop Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.
Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin

CONFIGURATIONS

iM2400
Standard

iM2400-X0000
No Foam

iM2400-X0002
With Padded Dividers

iM2400-X0001
With Foam

DIMENSIONS

Interior (L×W×D)	18.00 x 13.00" x 6.70 (45.7 x 33 x 17 cm)
Exterior (L×W×D)	19.20 x 15.20" x 7.30 (48.8 x 38.6 x 18.5 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	4.70" (11.9 cm)
Total Depth	6.7" (17 cm)
Int Volume	0.91 ft^3 (0.026 m^3)
Padlock Hole Diameter	0.38" (1 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

Black | OD Green | Yellow

WEIGHT

Weight With Foam	7.80 lbs (3.54 kg)
Weight Empty	6.50 lbs (2.95 kg)
Buoyancy	59.02 lbs (26.77 kg)
Master Pack Weight	28.30 lbs (12.84 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

IP67

OTHER

Master Pack	3
Military	yes

ACCESSORIES

iM24XX-PHOTOPALLET
Photography Pallet

iM24XX-LIDORG
Lid Organizer



iM2400-FOAM
4 pc. Replacement Foam Set

iM2400-DIV
Padded Divider Set

iM-STRAP-S-VER2
Padded Shoulder Strap

iM-LIDSTAY
Lid Stay



iM2400-TREK
TrekPak Case Divider Kit

1506TSA
TSA Lock

1500D
Desiccant Silica Gel

iM2400-M4-BEZEL-L
Lid Bezel Kit (Metric)



iM2400-MBEZ-B
Base Bezel Kit (Metric)

IM2400TPDIV
Extra TrekPak Dividers

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 10-23-26