



## iM3410

### Storm

Long Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- Five Press & Pull Latches
- Four Padlockable Hasps
- Three Double-layered, Soft-grip Handles
- Powerful Hinges
- O-ring seal
- Lightweight Strong HPX® Resin



## CONFIGURATIONS



**iM3410**  
Standard



**iM3410-X0000**  
No Foam



**iM3410-X0001**  
With Foam

## DIMENSIONS

<b>Interior (LxWxD)</b>	54.50 x 10.00" x 6.00 (138.4 x 25.4 x 15.2 cm)
<b>Exterior (LxWxD)</b>	57.74 x 12.71" x 6.67 (146.7 x 32.3 x 16.9 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	4.00" (10.2 cm)
<b>Total Depth</b>	6" (15.2 cm)
<b>Int Volume</b>	1.89 ft <sup>3</sup> (0.054 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.37" (0.9 cm)

## MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Purge Body (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>Purge Vent</b>	Gortex membrane

## COLOURS

---

■ Black

## WEIGHT

---

**Weight With Foam** 20.00 lbs (9.07 kg)  
**Weight Empty** 18.00 lbs (8.16 kg)

## TEMPERATURE

---

**Minimum Temperature** -20°F (-28.9 °C)  
**Maximum Temperature** 140°F (60 °C)

## CERTIFICATIONS

---

**IP67**

## OTHER

---

**Master Pack** 1  
**Military** yes

## ACCESSORIES

---



**iM3410-FOAM**  
4 pc. Replacement Foam Set



**iM-LIDSTAY**  
Lid Stay



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 07-06-26