



# EURO-V-5U-L

## Euro-V

5U

The Euro-V Rack Case is a smooth-finished, rotomoulded case featuring a 19" wide EIA standard rack with depths of 610 mm and 760 mm, designed to support metric-mounted equipment via an industry-standard square hole pattern (M6).

Lightweight yet robust, the Peli Euro-V Rack Case offers medium-duty protection in a streamlined format. Built for rapid deployment, it incorporates wall-mounted cylindrical shock mounts that isolate sensitive equipment from shock and vibration. Its interstackable design ensures compatibility with Super-V and BlackBox rack cases, enabling seamless integration across mixed fleets.

Manufactured in Germany to reduce lead times, the Euro-V is available in nine sizes (4U to 10U), all with moulded-in stacking ribs, edge casters, and a steel rack frame - pre-configured for fast, dependable field use.

Euro-V Rack Cases are ideal for mission-critical applications where reliable protection in a lighter, more compact design is essential. When precision equipment needs to arrive intact and on schedule, trust the Peli Euro-V Rack Case to deliver.



- Made in Germany for faster delivery and reduced lead times
- Optimised for Metric Equipment - Features a steel rack with an industry-standard square hole pattern (M6 clip nuts available).
- Durable & Shock-Resistant - Equipped with cylindrical shock mounts for maximum protection.
- Varied Depths - Available in 610mm (24") and 762mm (30") depths.
- Enhanced Mobility - Designed with 8 black plastic handles and edge casters for easy transport.

## DIMENSIONS

---

<b>Exterior (LxWxD)</b>	45.00 x 24.68" x 15.31 (114.3 x 62.7 x 38.9 cm)
<b>Rack Height</b>	19.00" (48.3 cm)
<b>Rack Depth</b>	30.00" (76.2 cm)
<b>Interior Lid Depth</b>	1.97" (5 cm)
<b>Interior Back Lid Depth</b>	4.72" (12 cm)

## MATERIALS

## COLOURS

- Black

## WEIGHT

---

<b>Weight</b>	52.91 lbs (24 kg)
---------------	-------------------

---

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 06-10-26