



# 1770

## Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Also available from Peli: The 1740 Long Case
- Four extra-deep base-to-lid locking cleats that ensure maximum stacking stability
- Watertight, crushproof, and dustproof
- 4-piece foam set
- O-ring seal
- Open cell core, polymer wall construction
- Stainless steel hardware and padlock protectors
- Two Integrated Automatic Pressure Equalization Valves
- Two rugged double-wide handles
- Wide-track polyurethane wheels with ball bearings and nylon hubs
- Comfortable rubber over-molded side-carry handle



### CONFIGURATIONS



**1770**  
Standard



**1770NF**  
No Foam



**1770WF**  
With Foam

### DIMENSIONS

<b>Interior (LxWxD)</b>	54.58 x 15.58" x 8.63 (138.6 x 39.6 x 21.9 cm)
<b>Exterior (LxWxD)</b>	57.42 x 18.48" x 10.50 (145.8 x 46.9 x 26.7 cm)
<b>Lid Depth</b>	1.65" (4.2 cm)
<b>Bottom Depth</b>	6.75" (17.1 cm)
<b>Total Depth</b>	8.4" (21.3 cm)
<b>Int Volume</b>	4.25 ft <sup>3</sup> (0.12 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.31" (0.8 cm)

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Purge Body</b>	ABS

**Purge Vent**

3 Micron Hydrophobic Non-Woven

## COLOURS

---

■ Black

## WEIGHT

---

<b>Weight With Foam</b>	41.49 lbs (18.82 kg)
<b>Weight Empty</b>	36.01 lbs (16.33 kg)
<b>Buoyancy</b>	280.00 lbs (127.01 kg)
<b>Master Pack Weight</b>	39.50 lbs (17.92 kg)

## TEMPERATURE

---

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	190°F (87.8 °C)

## OTHER

---

**Master Pack** 1

## ACCESSORIES

---



**1771**  
4 pc. Replacement Foam Set



**1773**  
Replacement O-ring



**1630DC**  
Document Container  
Accessory



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

### **Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 04-23-26*