



## iM2275

### Storm

Give your gear extra space. With a deeper lid, the iM2275 is the first case in our Peli™ Storm Case™ line that gives you more vertical space to work with for your equipment. This case gives you the freedom to configure multiple 4K cameras, diagnostic circuit readers, or a drone with accessories.

- **Watertight, crushproof, and dustproof**

- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



### CONFIGURATIONS



**iM2275**  
Standard



**iM2275-X0000**  
No Foam



**iM2275-X0006**  
With TrekPak Divider System



**iM2275-X0001**  
With Foam

### DIMENSIONS

|                              |                                               |
|------------------------------|-----------------------------------------------|
| <b>Interior (L×W×D)</b>      | 14.12 x 13.19" x 9.90 (35.9 x 33.5 x 25.1 cm) |
| <b>Exterior (L×W×D)</b>      | 15.25 x 15.50" x 10.22 (38.7 x 39.4 x 26 cm)  |
| <b>Lid Depth</b>             | 3.20" (8.1 cm)                                |
| <b>Bottom Depth</b>          | 6.30" (16 cm)                                 |
| <b>Total Depth</b>           | 9.5" (24.1 cm)                                |
| <b>Int Volume</b>            | 1.07 ft <sup>3</sup> (0.03 m <sup>3</sup> )   |
| <b>Padlock Hole Diameter</b> | 0.37" (0.9 cm)                                |

### MATERIALS

|                         |                                              |
|-------------------------|----------------------------------------------|
| <b>Body</b>             | Injection Molded HPX™ high performance resin |
| <b>Latch</b>            | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Latch (Alt)</b>      | Xenoy - Polyester/Polycarbonate blend        |
| <b>O-Ring</b>           | EPDM                                         |
| <b>Pins</b>             | Stainless Steel                              |
| <b>Pins (Alt)</b>       | Aluminum                                     |
| <b>Foam</b>             | 1.3/1.35 polyester                           |
| <b>Purge Body</b>       | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Body (Alt)</b> | Xenoy - Polyester/Polycarbonate blend        |
| <b>Purge Vent</b>       | Gortex membrane                              |

COLOURS

■ Black

WEIGHT

|                  |                     |
|------------------|---------------------|
| Weight With Foam | 10.25 lbs (4.6 kg)  |
| Weight Empty     | 8.00 lbs (3.6 kg)   |
| Buoyancy         | 68.80 lbs (31.2 kg) |

TEMPERATURE

|                     |                  |
|---------------------|------------------|
| Minimum Temperature | -20°F (-28.9 °C) |
| Maximum Temperature | 140°F (60 °C)    |

CERTIFICATIONS

IP67

OTHER

|             |     |
|-------------|-----|
| Master Pack | 3   |
| Military    | yes |

ACCESSORIES



**iM-STRAP-S-VER2**  
Padded Shoulder Strap



**iM-LIDSTAY**  
Lid Stay



**iM2275-FOAM**  
4 pc. Replacement Foam Set



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**iM2275-M4-BEZE-L**  
Lid Bezel Kit (Metric)



**iM2275-MBEZ-B**  
Base Bezel Kit (Metric)