



1030 Micro

From small sensitive components to smartphones, protect your gear from the elements in a crushproof, watertight, & dustproof Micro Case from Peli.

- ***Case is able to be submerged under 1 meter of water for up to 30 minutes in accordance with IP67 testing parameters**
- **Available in clear with color liner or solid**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Carabiner
- Easy open latch
- Rubber liner for extra protection doubles as o-ring seal
- Peli's legendary lifetime guarantee**
- * Where applicable by law



DIMENSIONS

| | |
|-------------------------|--|
| Interior (LxWxD) | 6.37 x 2.62" x 2.06 (16.2 x 6.7 x 5.2 cm) |
| Exterior (LxWxD) | 7.50 x 3.87" x 2.43 (19.1 x 9.8 x 6.2 cm) |
| Lid Depth | 0.69" (1.8 cm) |
| Bottom Depth | 1.25" (3.2 cm) |
| Total Depth | 1.94" (4.9 cm) |
| Int Volume | 0.02 ft ³ (0.001 m ³) |

MATERIALS

| | |
|-------------------|--------------------------------------|
| Body | Polycarbonate (PC) |
| Latch | Xylex |
| O-Ring | Thermoplastic Rubber |
| Pins | Stainless Steel |
| Foam | TL - 426 4 lb. Esther |
| Purge Body | Polycarbonate (PC) |
| Purge Vent | Polyester Spun-Bond ePTFE Oleophobic |

COLOURS

| | | | |
|------------------|----------------|----------|-----------------|
| ■ Black | ■ Red | ■ Yellow | ■ Black - Clear |
| ■ Yellow - Clear | ■ Blue - Clear | | |

WEIGHT

| | |
|---------------------------|--------------------|
| Weight With Foam | 0.61 lbs (0.28 kg) |
| Weight Empty | 0.60 lbs (0.27 kg) |
| Buoyancy | 0.99 lbs (0.45 kg) |
| Master Pack Weight | 4.24 lbs (1.92 kg) |

TEMPERATURE

| | |
|----------------------------|------------------|
| Minimum Temperature | -10°F (-23.3 °C) |
| Maximum Temperature | 199°F (92.8 °C) |

CERTIFICATIONS

IP67

OTHER

| | |
|---------------------|-----|
| Minimum Pack | 6 |
| Master Pack | 6 |
| Military | yes |

ACCESSORIES



1032
Pick N Pluck™ Foam Insert

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 06-07-26