

9480

Remote Area Lighting Systems from Peli are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Peli tough
- 3 pre-set light output levels
- Up to 4,000 lumens (calculated)
- Up to 28 hrs of run time
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply



DIMENSIONS

Head (L×W×D) 8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm) Closed (L×W×D) 15.50 x 6.50" x 10.25 (39.4 x 16.5 x 26 cm)

Light Head Height

(max)

23.75" (60.3 cm)

MATERIALS

Body Polypropylene Aluminum Head Mast Aluminum

Polycarbonate (PC) Lens

COLOURS

Black Yellow

LIGHT SPECS

Lumens (High) 4000 Lumens (Med) 3000 1000 Lumens (Low) **Lamp Heads** 1 **Lamp Type** LED Number of LEDs 8 **Beam Spread** 125° **IP Rating** 54

POWER

Run Time (High) 6.00 hrs Run Time (Med) 8.00 hrs Run Time (Low) 28.00 hrs

Battery Type Sealed Lead Acid (SLA) RechargeableyesBattery Lifespan500 cyclesCharge Time8 hrs

Battery Level Indicator Full-time battery level display and low battery warning (visible flashing)

Sockets (Primary) 1 Volts 12.0v

WEIGHT


Weight 27.50 lbs (12.5 kg)

SWITCH

Switch Type Silicone Rubber Keypad
Light Modes High / Medium / Low / Flashing

ACCESSORIES







9483 Power Supply



9487 Padded Shoulder Strap



9489 Powerpack

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 09-02-25