# 9430

Remote Area Lighting Systems from Peli are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Peli tough
- New improved version - Generation 3
- Up to 15 hours of run time
- 3000 lumens of brightness
- Fully extendable mast with 360 degree rotating head
- Low Battery Warning System
- Waterproof Rubber Activation Switch
- Mast Extension Lock
- RoHS and CE Compliant
- Includes 110 – 240 Volt (50/60hz) charger and universal adaptors




## DIMENSIONS

| | |
|---|---|
| **Head (L×W×D)** | 6.50 x 7.87" x 2.56 (16.5 x 20 x 6.5 cm) |
| **Closed (L×W×D)** | 15.75 x 7.87" x 9.06 (40 x 20 x 23 cm) |
| **Light Head Height (max)** | 32.28" (82 cm) |
| **Cord Length** | 13.78" (35 cm) |

## MATERIALS

| | |
|---|---|
| **Body** | Polycarbonate (PC) / ABS |
| **Head** | Polycarbonate (PC) / ABS |
| **Mast** | Glass-Reinforced Plastic |
| **Lens** | Polycarbonate (PC) |

## COLOURS

Black

Yellow

## LIGHT SPECS

| | |
|---|---|
| **Lumens (High)** | 3000 |
| **Lumens (Low)** | 1500 |
| **Lamp Heads** | 1 |
| **Lamp Type** | LED |
| **Number of LEDs** | 6 |
| **Beam Spread** | 125° |
| **IP Rating** | 54 |

## POWER

| | |
|---|---|
| **Run Time (High)** | 8.00 hrs |
| **Run Time (Low)** | 15.00 hrs |
| **Battery Type** | Sealed Lead Acid (SLA) |
| **Rechargeable** | yes |
| **Battery Lifespan** | 500 cycles |
| **Battery Level Indicator** | Intermittent Blinking |
| **Sockets (Primary)** | 1 |
| **Sockets (Aux)** | 1 |
| **Volts** | 12.0v |

## WEIGHT

**Weight** 22.65 lbs (10.27 kg)

## SWITCH

**Switch Type** Silicone Rubber Keypad

## ACCESSORIES



**1460AALG**
1460 Case with custom fit foam



**9430TP**
Tripod



**9436B**
12/24V Vehicle Charger



**9437B**
Extension Cord (black connector)
118in (3m)

**Peli**
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

*Document created on 11-10-26*