



3415MZ0

Right Angle Light

The intrinsically safe work light packed with features and a magnet

The 3415MZ0 is the ultimate ATEX safety-certified compact work light. The Zone 0 (Category 1) certification provides the security needed for almost all hazardous locations. Driven by only 3AA batteries, the 3415MZ0 is equipped with both a spot and flood LED. This allows for close up as well as distant lighting needs. It is engineered to run on either or both LEDs. The articulating head and built in clip provide hands free and handheld options so you can direct the light wherever it is needed. The 3415MZ0 includes an integrated magnet expanding its hands free applications, truly a multi-task torch designed to bring great value to your lighting needs.

- Articulating Light Head
- Attached clip with integrated magnet
- Security Lanyard
- ATEX Zone 0 (Category 1) certified
- Split ring installed
- 2 modes: spot, flashing




DIMENSIONS

Length	7.44" (18.9 cm)
---------------	-----------------

MATERIALS

Body	Anti-static Impact Modified PC/PBT
O-Ring	NBR
Lens	Anti-static coated Polycarbonate (PC)
Shroud	Anti-static Impact Modified PC/PBT
Clip	Anti-static Impact Modified PC/PBT
Contact Spring Retainer	Stainless Steel / Phosphore Bronze / Brass Nickel Plate

COLOURS

 High Visibility Yellow
--

LIGHT SPECS

Lamp Type	LED
Lamp Secondary Type	LED

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	3
Volts	4.5v

WEIGHT

Weight With Batteries	9.6 oz (272 gr)
Weight Without Batteries	7.1 oz (201 gr)

SWITCH

Switch Type	Push Button
Light Modes	High / Flashing

CERTIFICATIONS

ATEX Zone 0
IECEX ia

FL1 STANDARD	SPOT / FLOOD	FLOOD	SPOT
	329 LUMENS	174 LUMENS	185 LUMENS
	6h 0mins	15h 0mins	14h 0mins
	133m	38m	134m
	4425cd	354cd	4517cd
	IPX8 (1m)		

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 01-22-26