



## 3335RZ0

The Peli™ 3335RZ0 is a small & light rechargeable intrinsically safe torch certified for ATEX/UKEX Zone 0 applications.

The 3335RZ0 boasts performance built in providing up to 246 lumens or up to 58 hours of continuous run time, and 3 light modes are provided: High, Low and Flashing. There is a full-time battery level indicator built into the power switch, so you'll always know when it's time to recharge. The Right-Angle Adapter accessory (#3317, sold separately) transforms the torch into a wearable work torch that allows the head to articulate, directing the light exactly where you need it.

- Full Time Battery Level Indication
- 3 modes High / Strobe / Low
- Lanyard (included)
- ATEX Safety Certified Zone 0 (Cat. 1)
- IP67 Rating
- Up to 246 Lumens
- Right-Angle Accessory (#3317, sold separately) transforms the 3335R into hands free wearable flashlight with head rotation capability
- Up to 58 hours run time
- Lithium-Ion rechargeable battery included



### DIMENSIONS

|               |                 |
|---------------|-----------------|
| <b>Length</b> | 6.11" (15.5 cm) |
|---------------|-----------------|

### MATERIALS

|               |                                       |
|---------------|---------------------------------------|
| <b>Body</b>   | Anti-static Impact Modified PC/PBT    |
| <b>O-Ring</b> | EPDM                                  |
| <b>Lens</b>   | Anti-static coated Polycarbonate (PC) |
| <b>Shroud</b> | Anti-static Impact Modified PC/PBT    |
| <b>Clip</b>   | Stainless Steel                       |

### COLOURS



Yellow

### LIGHT SPECS

|                  |     |
|------------------|-----|
| <b>Lamp Type</b> | LED |
|------------------|-----|

### POWER

|                                |             |
|--------------------------------|-------------|
| <b>Battery Size</b>            | 18650       |
| <b>Battery Type</b>            | Lithium-Ion |
| <b>Battery Quantity</b>        | 1           |
| <b>Batteries Included</b>      | yes         |
| <b>Rechargeable</b>            | yes         |
| <b>Charge Time</b>             | 12 hrs      |
| <b>Battery Level Indicator</b> | RGB LED     |
| <b>Volts</b>                   | 3.7v        |

WEIGHT






|                          |                 |
|--------------------------|-----------------|
| Weight With Batteries    | 4.6 oz (130 gr) |
| Weight Without Batteries | 3.0 oz (85 gr)  |

SWITCH

|             |                       |
|-------------|-----------------------|
| Switch Type | Push Button           |
| Light Modes | High / Low / Flashing |

CERTIFICATIONS

|             |
|-------------|
| ATEX Zone 0 |
| IECEX ia    |

| FL1 STANDARD                                                                        | HIGH       | LOW       |
|-------------------------------------------------------------------------------------|------------|-----------|
|    | 246 LUMENS | 30 LUMENS |
|   | 6h 15mins  | 58h 0mins |
|  | 151m       | 51m       |
|  | 5718cd     | 649cd     |
|  | IP67       |           |

ACCESSORIES



**3317**  
Right Angle Adapter

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 09-08-25*